

MA212 PCB Terminal Block, Modular




Dimensions/Positions

MA212-350M

間距	Pitch	3.50mm
尺寸a	Dimension a	3.50mm
長度 A	Length	A= 3.5xP(P≥2)
塑膠本體	Housing Material	PA 66
彈片	Spring	Stainless Strip Steel
端子	Contact	Brass, Tin Plated
螺紋	Screw Thread	M2.0, Steel, Zinc Plated
電線線徑	Wire Size	16 ~ 26AWG
PCB孔徑	PCB Hole Diameter	1.2mm
最大緊固扭距	Tightening Torque, Max.	2.5 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	2.5 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	2.5 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	2.5 kV
額定電壓(III/3)	Rated voltage(III/3)	160V
額定電壓(III/2)	Rated voltage(III/2)	200V
額定電壓(II/2)	Rated voltage(II/2)	400V
絕緣材料	Insulating Material	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	300V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	6A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	300V
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	6A



PCB Layout

