

MB322 PCB Terminal Block, Modular



Dimensions/Positions

MB322-762M

| | | |
|--------|-------------------------|--------------------------|
| 間距 | Pitch | 7.62mm |
| 尺寸a | Dimension a | 7.62mm |
| 長度 A | Length | A= 7.62xP(P≥2) |
| 塑膠本體 | Housing Material | PA 66 |
| 壓線圈 | Cage Clamp | Brass, Ni Plated |
| 端子 | Contact | Brass, Tin Plated |
| 螺紋 | Screw Thread | M2.6, Steel, Zinc Plated |
| 電線線徑 | Wire Size | 12 ~ 26AWG |
| PCB孔徑 | PCB Hole Diameter | 1.5mm |
| 最大緊固扭距 | Tightening Torque, Max. | 5.0 Lb-in |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C |

TECHNICAL DATA

| | | |
|------------------|---|--------------------|
| 絕緣材料組 | Insulating Material group | I |
| 額定電涌電壓(III/3) | Rated surge voltage (III/3) | 6 kV |
| 額定電涌電壓(III/2) | Rated surge voltage (III/2) | 6 kV |
| 額定電涌電壓(II/2) | Rated surge voltage (II/2) | 6 kV |
| 額定電壓(III/3) | Rated voltage(III/3) | 500V |
| 額定電壓(III/2) | Rated voltage(III/2) | 630V |
| 額定電壓(II/2) | Rated voltage(II/2) | 1000V |
| 連接符合標準 | Connection in acc. with standard EN-VDE | |
| 額定電流 I_N | Nominal Current I_N | 16A |
| 額定橫截面 | Nominal Cross Section | 2.5mm ² |
| 最大負載電流 | Maximum load current | 16A |
| 絕緣材料 | Insulating Material | PA |
| 阻燃等級, 符合UL94 | Inflammability class acc. to UL94 | V0 |
| 額定電壓, UL/CUL標準B組 | Nominal voltage, UL/CUL Use Group B | 300V |
| 額定電流, UL/CUL標準B組 | Nominal current, UL/CUL Use Group B | 16A |
| 額定電壓, UL/CUL標準C組 | Nominal voltage, UL/CUL Use Group C | 300V |
| 額定電流, UL/CUL標準C組 | Nominal current, UL/CUL Use Group C | 16A |

