

MC600, MC605 Pluggable PCB Connector, Plug



Dimensions/Positions

		MC600-350	MC605-350
間距	Pitch	3.50mm	3.50mm
尺寸a	Dimension a	3.50mm	3.50mm
長度 A	Length	A= 3.50xP(P≥4)	A= 3.50xP+15.64mm(P≥4)
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
導電夾片	Contact	Phosphor Bronze, Tin Plated	Phosphor Bronze, Tin Plated
電線線徑	Wire Size	18 ~ 22AWG	18 ~ 22AWG
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	8 kV	8 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	8 kV	8 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	8 kV	8 kV
額定電壓(III/3)	Rated voltage(III/3)	500V	500V
額定電壓(III/2)	Rated voltage(III/2)	800V	800V
額定電壓(II/2)	Rated voltage(II/2)	1000V	1000V
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	150V	150V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	5A	5A

