

MD122 Connector, Header



Dimensions/Positions

MD122-500

間距	Pitch	5.00mm
尺寸a	Dimension a	5.00mm
長度 A	Length	A= 5.00xP(P≥2)
焊針	Pin Dimensions	Brass, Tin Plated
塑膠本體	Housing Material	PA 66
PCB孔徑	PCB Hole Diameter	1.2mm
環境作業溫度	Operating Temperature	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	2.5kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	2.5kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	2.5kV
額定電壓(III/2)	Rated voltage(III/2)	250V
額定電壓(II/2)	Rated voltage(II/2)	250V
絕緣材料	Insulating Material	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	300V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	15A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	300V
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	15A

