



ME020, ME030 PCB Connector, Header



Dimensions/Positions

		ME020-762	ME030-250
間距	Pitch	7.62mm	2.50mm
尺寸a	Dimension a	7.62mm	2.50mm
長度 A	Length	A= 7.62xP-1.80mm(P≥2)	A= 2.50xP+ 4.40mm(P≥4)
焊針	Pin Dimensions	Brass, Tin Plated	Brass, Tin Plated
塑膠本體	Housing Material	PA 66	PA 66
PCB孔徑	PCB Hole Diameter	1.5mm	1.2mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	6 kV	1.5 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	6 kV	2.5 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	6 kV	2.5 kV
額定電壓(III/3)	Rated voltage(III/3)	400V	-
額定電壓(III/2)	Rated voltage(III/2)	630V	160V
額定電壓(II/2)	Rated voltage(II/2)	1000V	320V
連接符合標準	Connection in acc. with standard EN-VDE		
額定電流I _N	Nominal Current I _N	16A	-
額定橫截面	Nominal Cross Section	4.0mm ²	-
最大負載電流	Maximum load current	16A	-
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	300V	125V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	15A	4A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	300V	-
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	15A	-

