

ME030 PCB Connector, Header




Dimensions/Positions



		ME030-350	ME030-381
間距	Pitch	3.50mm	3.81mm
尺寸a	Dimension a	3.50mm	3.81mm
長度 A	Length	$A = 3.50 \times P + 0.6 \text{mm} (P \geq 2)$	$A = 3.81 \times P + 0.6 \text{mm} (P \geq 2)$
焊針	Pin Dimensions	Brass, Tin Plated	Brass, Tin Plated
塑膠本體	Housing Material	PA 66	PA 66
PCB孔徑	PCB Hole Diameter	1.3mm	1.3mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	3 kV	4 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	3 kV	4 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	3 kV	4 kV
額定電壓(III/3)	Rated voltage(III/3)	160V	200V
額定電壓(III/2)	Rated voltage(III/2)	250V	320V
額定電壓(II/2)	Rated voltage(II/2)	400V	400V
連接符合標準	Connection in acc. with standard EN-VDE		
額定電流 I_N	Nominal Current I_N	10A	10A
額定橫截面	Nominal Cross Section	1.5mm ²	1.5mm ²
最大負載電流	Maximum load current	10A	10A
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	300V	300V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	10A	10A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	300V	300V
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	10A	10A



PCB Layout



PCB Layout

