





# MF203, MF204 Connector



ME203-381



ME204-381



## Dimensions/Positions

|        |                       | MF203-381                   | MF204-381                   |
|--------|-----------------------|-----------------------------|-----------------------------|
| 間距     | Pitch                 | 3.81mm                      | 3.81mm                      |
| 尺寸a    | Dimension a           | 3.81mm                      | 3.81mm                      |
| 長度 A   | Length                | A=3.81xP+0.80mm(P≥2)        | A=3.81xP+0.80mm(P≥2)        |
| 塑膠本體   | Housing Material      | PA 66                       | PA 66                       |
| 夾片     | Wire Protector        | Phosphor Bronze, Tin Plated | Phosphor Bronze, Tin Plated |
| PCB孔徑  | PCB Hole Diameter     | 1.6mm                       | 1.6mm                       |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C             | -40°C to +105°C             |

## TECHNICAL DATA

|               |                                   | I      | I      |
|---------------|-----------------------------------|--------|--------|
| 絕緣材料組         | Insulating Material group         | I      | I      |
| 額定電涌電壓(III/3) | Rated surge voltage (III/3)       | 2.5 kV | 2.5 kV |
| 額定電涌電壓(III/2) | Rated surge voltage (III/2)       | 2.5 kV | 2.5 kV |
| 額定電涌電壓(II/2)  | Rated surge voltage (II/2)        | 2.5 kV | 2.5 kV |
| 額定電壓(III/2)   | Rated voltage(III/2)              | 160V   | 160V   |
| 額定電壓(II/2)    | Rated voltage(II/2)               | 320V   | 320V   |
| 絕緣材料          | Insulating Material               | PA     | PA     |
| 阻燃等級, 符合UL94  | Inflammability class acc. to UL94 | V0     | V0     |
| 額定電壓          | Nominal voltage                   | 300V   | 300V   |
| 額定電流          | Nominal current                   | 7A     | 7A     |

