





MF203, MF204 Connector



ME203-381



ME204-381



Dimensions/Positions

		MF203-381	MF204-381
間距	Pitch	3.81mm	3.81mm
尺寸a	Dimension a	3.81mm	3.81mm
長度 A	Length	A=3.81xP+0.80mm(P≥2)	A=3.81xP+0.80mm(P≥2)
塑膠本體	Housing Material	PA 66	PA 66
夾片	Wire Protector	Phosphor Bronze, Tin Plated	Phosphor Bronze, Tin Plated
PCB孔徑	PCB Hole Diameter	1.6mm	1.6mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

		I	I
絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	2.5 kV	2.5 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	2.5 kV	2.5 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	2.5 kV	2.5 kV
額定電壓(III/2)	Rated voltage(III/2)	160V	160V
額定電壓(II/2)	Rated voltage(II/2)	320V	320V
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓	Nominal voltage	300V	300V
額定電流	Nominal current	7A	7A

