

MPC 300 Connector



Dimensions/Positions

MPC300-508

間距	Pitch	5.08mm
尺寸a	Dimension a	5.08mm
長度 A	Length	A = 5.08xP (P ≥ 2)
塑膠本體	Housing Material	PA 66
夾片	Contact	Copper, Tin Plated
彈片	Wire Protector	Stainless Strip Steel
電線線徑	Wire Size	12 ~ 26AWG
環境作業溫度	Operating Temperature	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	2.5 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	2.5 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	2.5 kV
額定電壓(III/2)	Rated voltage(III/2)	160V
額定電壓(II/2)	Rated voltage(II/2)	320V
絕緣材料	Insulating Material	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	300V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	16A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	300V
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	10A

