

MWX100 PCB Spring Type Terminal Block



Dimensions/Positions

		MWX100-250	MWX100-254
間距	Pitch	2.50mm	2.54mm
尺寸a	Dimension a	2.50mm	2.54mm
長度 A	Length	A= 2.50xP+1.50mm(P≥2)	A= 2.54xP+1.50mm(P≥2)
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
電線線徑	Wire Size	20 ~ 28AWG	20 ~ 28AWG
端蓋	Cover	PA 66	PA 66
PCB孔徑	PCB Hole Diameter	1.3mm	1.3mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C
TECHNICAL DATA			
絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	2.5 kV	2.5 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	2.5 kV	-
額定電涌電壓(II/2)	Rated surge voltage (II/2)	2.5 kV	2.5 kV
額定電壓(III/3)	Rated voltage(III/3)	63V	63V
額定電壓(II/2)	Rated voltage(II/2)	320V	320V
連接符合標準	Connection in acc. with standard EN-VDE		
額定電流I _N	Nominal Current I _N	6A	6A
額定橫截面	Nominal Cross Section	0.5mm ²	0.5mm ²
最大負載電流	Maximum load current	6A	6A
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	150V	150V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	4A	4A

