

MWX101 PCB Spring Type Terminal Block



Dimensions/Positions

MWX101-016

間距	Pitch	10.16mm
尺寸a	Dimension a	10.16mm
長度 A	Length	A= 10.16xP-4.08mm(P≥2)
塑膠本體	Housing Material	PA 66
彈片	Spring	Stainless Strip Steel
端子	Contact	Brass, Tin Plated
電線線徑	Wire Size	14 ~ 28AWG
端蓋	Cover	PA 66
PCB孔徑	PCB Hole Diameter	1.3mm
環境作業溫度	Operating Temperature	-40°C to +105°C
TECHNICAL DATA		
絕緣材料組	Insulating Material group	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	6 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	6 kV
額定電壓(III/3)	Rated voltage(III/3)	500V
額定電壓(II/2)	Rated voltage(II/2)	1000V
絕緣材料	Insulating Material	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	300V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	16A

