

MWX211 PCB Spring Type Terminal Block, with Lever

 MWX211-381		 MWX211-500	
			
Dimensions/Positions		MWX211-381	MWX211-500
間距	Pitch	3.81mm	5.00mm
尺寸a	Dimension a	3.81mm	5.00mm
長度 A	Length	A= 3.81xP +1.50mm(P≥2)	A= 5.00xP+1.50mm(P≥2)
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
電線線徑	Wire Size	12 ~ 22AWG	14 ~ 20AWG
端蓋	Cover	PA 66	PA 66
PCB孔徑	PCB Hole Diameter	1.2mm	1.2mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C
TECHNICAL DATA			
絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	4 kV	4 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	4 kV	4 kV
額定電壓(III/3)	Rated voltage(III/3)	200V	250V
額定電壓(II/2)	Rated voltage(II/2)	500V	630V
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	300V	300V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	8A	10A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	-	300V
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	-	10A

