



MX322, MX422 Connector, Screwless



Dimensions/Positions

		MX322-254	MX422-254
間距	Pitch	2.54mm	2.54mm
尺寸a	Dimension a	2.54mm	2.54mm
長度 A	Length	A= 2.54xP+3.00mm(P≥2)	A= 2.54xP+3.00mm(P≥2)
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
端蓋	Cover	PA 66	PA 66
電線線徑	Wire Size	20 ~ 26AWG	20 ~ 26AWG
PCB孔徑	PCB Hole Diameter	1.2mm	1.2mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	2.5 kV	2.5 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	2.5 kV	2.5 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	2.5 kV	2.5 kV
額定電壓(III/3)	Rated voltage(III/3)	63V	63V
額定電壓(III/2)	Rated voltage(III/2)	160V	160V
額定電壓(II/2)	Rated voltage(II/2)	320V	320V
絕緣材料	Insulating Material	PA 66	PA 66
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	150V	150V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	6A	6A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	150V	150V
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	6A	6A

