

MX822 Connector, Screwless



Dimensions/Positions

MX822-457

間距	Pitch	4.57mm
尺寸a	Dimension a	4.57mm
長度 A	Length	A= 4.57xP+4.43mm(P≥2)
塑膠本體	Housing Material	PBT
端子	Contact	Phosphor Bronze, Tinplated
電線線徑	Wire Size	16 ~ 18AWG
PCB孔徑	PCB Hole Diameter	1.3mm
環境作業溫度	Operating Temperature	-40°C to +120°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	3 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	3 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	3 kV
額定電壓(III/3)	Rated voltage(III/3)	125V
額定電壓(III/2)	Rated voltage(III/2)	250V
額定電壓(II/2)	Rated voltage(II/2)	320V
絕緣材料	Insulating Material	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	150V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	9A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	300V
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	9A

