

# OM56001



## Dimensions/Positions

## OM56001

塑膠本體	Housing Material	PA 66
引腳尺寸	Pin Dimensions	Brass, Tin Plated
螺絲	Screws	Steel
電線線徑	Wire Size	14 ~ 24AWG
最大緊固扭距	Tightening Torque, Max.	4.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

## TECHNICAL DATA

絕緣材料組	Insulating Material group	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	4 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	4 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	4 kV
額定電壓(III/2)	Rated voltage(III/2)	320V
額定電壓(II/2)	Rated voltage(II/2)	630V
絕緣材料	Insulating Material	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	250V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	12A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	300V
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	10A

