



OMC021, OMC101 Pluggable PCB Connector, Plug



OMC021-508



OMC101-508



Dimensions/Positions


OMC021-508

OMC101-508

間距	Pitch	5.08mm	5.08mm
尺寸a	Dimension a	5.08mm	5.08mm
長度 A	Length	A= 5.08xP+21.08mm(P≥2)	A= 5.08xP+10.16mm(P≥2)
塑膠本體	Housing Material	PA 66	PA 66
壓線圈	Cage Clamp	Brass, Ni Plated	Brass, Ni Plated
導電夾片	Contact	Phosphor Bronze, Tin Plated	Phosphor Bronze, Tin Plated
螺紋	Screw Thread	M2.6, Steel, Zinc Plated	M3.0, Steel, Zinc Plated
電線線徑	Wire Size	12 ~ 24AWG	12 ~ 24AWG
最大緊固扭矩	Tightening Torque, Max.	4.5 Lb-in	4.5 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

絕緣材料組	Insulating Material group	I	I
額定電涌電壓(III/3)	Rated surge voltage (III/3)	3 kV	5 kV
額定電涌電壓(III/2)	Rated surge voltage (III/2)	3 kV	5 kV
額定電涌電壓(II/2)	Rated surge voltage (II/2)	3 kV	5 kV
額定電壓(III/3)	Rated voltage(III/3)	100V	250V
額定電壓(III/2)	Rated voltage(III/2)	200V	400V
額定電壓(II/2)	Rated voltage(II/2)	320V	630V
絕緣材料	Insulating Material	PA	PA
阻燃等級, 符合UL94	Inflammability class acc. to UL94	V0	V0
額定電壓, UL/CUL標準B組	Nominal voltage, UL/CUL Use Group B	250V	300V
額定電流, UL/CUL標準B組	Nominal current, UL/CUL Use Group B	10A	16A
額定電壓, UL/CUL標準D組	Nominal voltage, UL/CUL Use Group D	250V	-
額定電流, UL/CUL標準D組	Nominal current, UL/CUL Use Group D	10A	-



Note:
 Screw Plating: Changes are available upon request
 Cage Clamp: OMC 100#: Steel